

NORMAL PROCEDURES

TABLE OF CONTENTS

	page
Introduction	N-ii
Speeds for Normal Operations	N-ii

CHECKLIST PROCEDURES

Preflight Inspection	N-2
Cabin	N-2
Empennage	N-3
Right Wing, Trailing Edge	N-3
Right Wing	N-3
Nose	N-3
Left Wing	N-4
Left Wing, Leading Edge	N-4
Left Wing, Trailing Edge	N-4
<i>Starting</i>	N-5
Prepare for Starting	N-5
Before Starting Engine	N-5
Starting Engine (Temperatures Above Freezing)	N-6
<i>Taxi</i>	N-6
Before Takeoff	N-7
Takeoff	N-7
Normal Takeoff	N-7
Short Field Takeoff	N-8
<i>Soft Field Takeoff</i>	N-8
Enroute Climb	N-8
Cruise	N-8
Descent	N-9
Before Landing	N-9
Landing	N-9
Normal Landing	N-9
Short Field Landing	N-9
<i>Soft Field Landing</i>	N-9
Balked Landing	N-10
After Landing	N-10

Securing Airplane	N-10
Parking Airplane	N-10

INTRODUCTION

Cessna 152 Information Manual Section 4 provides checklist and amplified procedures for the conduct of normal operations. Normal procedures associated with optional systems can be found in *Cessna 152 Information Manual* Section 9.

SPEEDS FOR NORMAL OPERATIONS

Unless otherwise noted, the following speeds are based on a maximum weight of 1670 pounds and may be used for any lesser weight.

Takeoff:

Normal Climb Out	65-75 KIAS
Short Field Takeoff, Flaps Up, Speed at 50 Feet	54 KIAS

Climb, Flaps Up:

Normal	70-80 KIAS
Best Rate-of-Climb, Sea Level	67 KIAS
Best Rate-of-Climb, 10,000 Feet	61 KIAS
Best Angle-of-Climb, Sea Level thru 10,000 Feet ...	55 KIAS

Landing Approach:

Normal Approach, Flaps Up	60-70 KIAS
Normal Approach, Flaps 30°	55-65 KIAS
Short Field Approach, Flaps 30°	54 KIAS

Balked Landing:

Maximum Power, Flaps 20°	55 KIAS
--------------------------------	---------


Maximum Recommended Turbulent Air Penetration Speed:

1670 Lbs	104 KIAS
1500 Lbs	98 KIAS
1350 Lbs	93 KIAS

Maximum Demonstrated Crosswind Velocity	12 KNOTS
---	----------

NOTE

Italic text in this checklist indicates a modification to the checklist in the Cessna 152 Information Manual.



NOTE

Visually check airplane for general condition during walk-around inspection. In cold weather, remove even small accumulations of frost, ice or snow from wing, tail and control surfaces. Also, make sure that control surfaces contain no internal accumulations of ice or debris. Prior to flight, check that pitot heater is warm to touch within 30 seconds with battery and pitot heat switches on. If a night flight is planned, check operation of all lights, and make sure a flashlight is available.

Preflight Inspection

CHECKLIST PROCEDURES

PREFLIGHT INSPECTION

(1) CABIN

1. Windshield -- CLEAN if required
2. Pitot Tube Cover -- REMOVE. Check for pitot blockage.
3. Nose Plugs -- REMOVE. Check for air intake blockage.
4. Documents/Hobbs/Tach -- CHECK
5. Cessna 152 Information Manual and Flyaway Notebook -- AVAILABLE IN THE AIRPLANE.
6. Control Wheel Lock -- REMOVE.
7. Ignition Switch -- OFF. Place keys on glare shield.
8. Avionics Master Switch -- OFF.
9. Master Switch -- ON.

WARNING

WHEN TURNING ON THE MASTER SWITCH, USING AN EXTERNAL POWER SOURCE, OR PULLING THE PROPELLER THROUGH BY HAND, TREAT THE PROPELLER AS IF THE IGNITION SWITCH WERE ON. DO NOT STAND, NOR ALLOW ANYONE ELSE TO STAND, WITHIN THE ARC OF THE PROPELLER, SINCE A LOOSE OR BROKEN WIRE, OR A COMPONENT MALFUNCTION, COULD CAUSE THE PROPELLER TO ROTATE.

10. Fuel Quantity Indicators -- CHECK QUANTITY
11. Flashing Beacon and Strobe -- CHECK
12. Interior Lights, Navigation Lights, and Landing Light -- CHECK for night operations
13. Flaps -- EXTEND.
14. Master Switch -- OFF.
15. Fuel Shutoff Valve -- ON.
16. Elevator Trim -- SET for takeoff.

(2) EMPENNAGE

1. Rudder Gust Lock *(if installed)* -- REMOVE.
2. Tail Tie-Down -- DISCONNECT.
3. Control Surfaces -- CHECK freedom of movement and security.
4. Trim Tab -- CHECK security.

(3) RIGHT WING Trailing Edge

1. Flap -- CHECK for security and condition.
2. Aileron -- CHECK freedom of movement and security.

(4) RIGHT WING

1. Wing Tie-Down -- DISCONNECT.
2. Main Wheel Tire -- CHECK for proper inflation *and general condition (weather checks, tread depth and wear, etc...)*.
3. Before first flight of the day and after each refueling, use sampler cup and drain small quantity of fuel from fuel tank sump quick-drain valve to check for water, sediment, and proper fuel grade. *If water is observed, take further samples until clear and then gently rock wings and lower tail to the ground to move any additional contaminants to the sampling points. Take repeated samples from all fuel drain points until all contamination has been removed. If contaminants are still present, refer to WARNING below and do not fly airplane.*

WARNING

IF, AFTER REPEATED SAMPLING, EVIDENCE OF CONTAMINATION STILL EXISTS, THE AIRPLANE SHOULD NOT BE FLOWN. TANKS SHOULD BE DRAINED AND SYSTEM PURGED BY QUALIFIED MAINTENANCE PERSONNEL. ALL EVIDENCE OF CONTAMINATION MUST BE REMOVED BEFORE FURTHER FLIGHT.

4. Fuel Quantity -- CHECK VISUALLY for desired level.
5. Fuel Filler Cap -- SECURE *and VENT UNOBSTRUCTED*.

(5) NOSE

1. Engine Oil Level -- CHECK, do not operate with less than four quarts. Fill to six quarts for extended flight.
RAFA Procedure: If below 4½ quarts – add 1 quart.
2. Before first flight of the day and after each refueling, pull out strainer drain knob for about four seconds to clear fuel strainer of possible water and sediment. Check strainer drain closed. If water is observed, the fuel system may contain additional water, and further draining of the system at the strainer, fuel tank sumps, and fuel line drain plug will be necessary. *If water is observed, take*

further samples until clear and then gently rock wings and lower tail to the ground to move any additional contaminants to the sampling points. Take repeated samples from all fuel drain points until all contamination has been removed. If contaminants are still present, refer to WARNING above and do not fly airplane.

3. Engine Cooling Air Inlets -- CLEAR of obstructions.
4. Propeller and Spinner -- CHECK for nicks and security.
5. Landing Light(s) (may be on wing) -- CHECK for condition and cleanliness.
6. Carburetor Air Filter -- CHECK for restrictions by dust or other foreign matter.
7. Nose Wheel Strut and Tire -- CHECK for proper inflation *of strut and general condition (weather checks, tread depth and wear, etc...) of tire*.
8. Nose Tie-Down *(if installed)* -- DISCONNECT.
9. Static Source Opening (left side of fuselage) -- CHECK for stoppage.

(6) LEFT WING

1. Main Wheel Tire -- CHECK for proper inflation *and general condition (weather checks, tread depth and wear, etc...)*.
2. Before first flight of the day and after each refueling, use sampler cup and drain small quantity of fuel from fuel tank sump quick-drain valve to check for water, sediment and proper fuel grade. *If water is observed, take further samples until clear and then gently rock wings and lower tail to the ground to move any additional contaminants to the sampling points. Take repeated samples from all fuel drain points until all contamination has been removed. If contaminants are still present, refer to WARNING above and do not fly airplane.*
3. Fuel Quantity -- CHECK VISUALLY for desired level.
4. Fuel Filler Cap -- SECURE *and VENT UNOBSTRUCTED*.

(7) LEFT WING Leading Edge

1. Pitot Tube Cover -- Verify REMOVED and check opening for stoppage.
2. Stall Warning Opening -- CHECK for stoppage. To check the system, place a clean handkerchief over the vent opening and apply suction; a sound from the warning horn will confirm system operation.
3. Fuel Tank Vent Opening -- CHECK for stoppage.
4. Wing Tie-Down -- DISCONNECT.

(8) LEFT WING Trailing Edge

1. Aileron-- CHECK for freedom of movement and security.
2. Flap -- CHECK for security and condition.

STARTING**PREPARE FOR STARTING**

1. *Surrounding Area -- CHECK for personnel and hazards. REMOVE chocks and tow bar.*
2. *Master Switch -- ON.*
3. *Avionics Master Switch -- ON.*
4. *Radios -- SET (comm and nav)*
5. *Weather -- CHECK (ATIS/ASOS/AWOS)*
6. *Avionics Master Switch -- OFF*
7. *Master Switch -- OFF*
8. *Passenger Briefing -- COMPLETE.*
9. *Flight Plan -- Open*

BEFORE STARTING ENGINE

1. *Preflight Inspection -- COMPLETE.*
2. *Seats, Seat Belts, Shoulder Harnesses -- ADJUST and LOCK.*
3. *Fuel Shutoff Valve -- ON.*
4. *Electrical Equipment -- OFF.*
5. *Avionics Master Switch -- OFF.*

CAUTION

The avionics master switch must be OFF during engine start to prevent possible damage to avionics.

6. *Brakes -- TEST and HOLD.*
7. *Circuit Breakers -- CHECK IN.*

STARTING ENGINE (Temperature Above Freezing)

NOTE

For cold weather starting procedures, use COLD WEATHER OPERATION procedures in Cessna 152 Information Manual, Section 4.

1. *Mixture -- RICH.*
2. *Carburetor Heat -- COLD.*
3. *Flashing Beacon -- ON.*
4. *Navigation Lights -- ON for night operations.*
5. *Prime -- AS REQUIRED (up to 3 strokes; none if engine is warm).*
6. *Throttle -- OPEN ½ INCH (CLOSED if engine is warm).*
7. *Propeller Area -- SHOUT "CLEAR PROP" and check propeller area.*
8. *Master Switch -- ON.*
9. *Ignition Switch -- START (release when engine starts).*
10. *Throttle -- ADJUST for 1000 RPM or less.*
11. *Oil Pressure -- CHECK.*
12. *Avionics Master Switch -- ON.*
13. *Navigation Lights -- ON (must be ON to power ADS-B).*
14. *Transponder -- SQUAWK 1200 ALT or ATC assigned code.*
15. *Flaps -- RETRACT (verify visually).*

TAXI – *Review checklist before movement, do not read while taxiing.*

1. *Throttle -- Maintain 1000 RPM for ground operations.*
2. *Radio -- REQUEST TAXI CLEARANCE or announce intentions.*
3. *Brakes -- CHECK during initial movement.*
4. *Nose Wheel Steering -- CHECK.*
5. *Ailerons -- POSITION for crosswind taxi.*
6. *Flight Instruments -- CHECK for proper movement during taxi.*

BEFORE TAKEOFF

1. *Brakes -- HOLD.*
2. Cabin Doors -- CLOSED and LATCHED.
3. *Seats, Seat Belts, Shoulder Harnesses -- CHECK SECURE.*
4. Flight Controls -- FREE and CORRECT.
5. Flight Instruments -- SET.
6. *Fuel Quantity -- CHECK.*
7. Fuel Shutoff Valve -- ON.
8. Mixture -- RICH (below 3000 feet).
9. Throttle -- 1700 RPM.
 - a. Magnetos -- CHECK (RPM drop should not exceed 125 RPM on either magneto or 50 RPM differential between magnetos).
 - b. Carburetor Heat -- CHECK (for RPM drop).
 - c. Engine Instruments and Ammeter -- CHECK.
 - d. Suction Gage -- CHECK.
10. Throttle -- 1000 RPM OR LESS.
11. Radios -- SET.
12. *Flashing Beacon and Navigation/Strobe Lights -- ON.*
13. Elevator Trim -- TAKEOFF.
14. Throttle Friction Lock -- ADJUST.
15. *Wing Flaps -- SET for takeoff.*
16. *Radio -- REQUEST TAKEOFF CLEARANCE or announce intentions.*
17. Brakes -- RELEASE.

TAKEOFF**NORMAL TAKEOFF**

1. Wing Flaps -- 0° - 10°.
2. Carburetor Heat -- COLD.
3. Throttle -- FULL OPEN.
4. *Mixture -- RICH (above 3000 feet, LEAN to obtain maximum RPM).*
5. Elevator Control -- LIFT NOSE WHEEL at 50 KIAS.
6. Climb Speed -- 65-75 KIAS.

SHORT FIELD TAKEOFF

1. Wing Flaps -- 10°.
2. Carburetor Heat -- COLD.
3. Brakes -- APPLY.
4. Throttle -- FULL OPEN.
5. Mixture -- RICH (above 3000 feet, LEAN to obtain maximum RPM).
6. Brakes -- RELEASE.
7. Elevator Control -- SLIGHTLY TAIL LOW.
8. Climb Speed -- 54 KIAS (until all obstacles are cleared).
9. Wing Flaps -- RETRACT slowly (*after reaching 60 KIAS and clear all obstacles*).

SOFT FIELD TAKEOFF

1. Wing Flaps -- 10°.
2. Carburetor Heat -- COLD.
3. Elevator -- FULL AFT.
4. Throttle -- FULL OPEN (*slowly*).
5. Mixture -- RICH (above 3000 feet, LEAN to obtain maximum RPM).
6. Roll -- *Maintain nose-high attitude with minimum weight on nose wheel.*
7. Elevator Control -- *LIFT AIRCRAFT off ground as soon as practical. LEVEL AIRCRAFT just above runway surface. ACCELERATE to appropriate airspeed for climb.*
8. Wing Flaps -- RETRACT slowly (*after reaching 60 KIAS and 50 feet*).

ENROUTE CLIMB

1. Airspeed -- 70-80 KIAS.

NOTE

If a maximum performance climb is necessary, use speeds shown in the Rate of Climb chart in *Cessna 152 Information Manual*, Section 5.

2. Throttle -- FULL OPEN.
3. Mixture -- RICH below 3000 feet, LEAN to obtain maximum RPM above 3000 feet.

CRUISE

1. Power -- 1900-2550 RPM (no more than 75%).
2. Elevator Trim -- ADJUST.
3. Mixture -- LEAN.

DESCENT

1. Mixture -- ADJUST for smooth operation (full rich for idle power).
2. Power -- AS DESIRED.
3. Carburetor Heat -- FULL HEAT AS REQUIRED

BEFORE LANDING

1. Seats, Seat Belts, Shoulder Harnesses -- ADJUST AND LOCK.
2. Mixture -- RICH.
3. Carburetor Heat -- ON (apply full heat before reducing power).

LANDING**NORMAL LANDING**

1. Airspeed -- 60-70 KIAS (flaps UP).
2. Wing Flaps -- AS DESIRED (below 85 KIAS).
3. Airspeed -- 55-65 KIAS (flaps DOWN).
4. Touchdown -- MAIN WHEELS FIRST.
5. Landing Roll -- LOWER NOSE WHEEL GENTLY.
6. Braking -- MINIMUM REQUIRED.

SHORT FIELD LANDING

1. Airspeed -- 60-70 KIAS (flaps UP) -- *Normal*.
2. Wing Flaps -- 30° (Below 85 KIAS).
3. Airspeed -- MAINTAIN 54 KIAS (*until flare*).
4. Power -- REDUCE to idle *as obstacle is cleared*.
5. Touchdown -- MAIN WHEELS FIRST.
6. Brakes -- APPLY HEAVILY -- **DO NOT LOCK THE BRAKES.**
7. Wing Flaps -- RETRACT.
8. Elevator -- *FULL NOSE UP (once firmly on ground)*.

SOFT FIELD LANDING

1. Airspeed -- 60-70 KIAS (flaps UP). -- *Normal*.
2. Wing Flaps -- 30° (Below 85 KIAS).
3. Airspeed -- 55-65 KIAS (flaps DOWN).
4. Power -- 1200-1300 RPM at touchdown.
5. Touchdown -- **SOFTLY ON MAIN WHEELS FIRST.**
6. Power -- **IDLE.**
7. Rollout -- *Maintain nose-high attitude with minimum weight on nose wheel.*
8. Brakes -- **NONE unless absolutely necessary.**

BALKED LANDING

1. Throttle -- FULL OPEN.
2. Carburetor Heat -- COLD.
3. Wing Flaps -- RETRACT TO 20°.
4. Airspeed -- 55 KIAS.
5. Wing Flaps -- RETRACT (*slowly after reaching 60 KIAS and clear all obstacles*).

AFTER LANDING

1. Wing Flaps -- UP.
2. Carburetor Heat -- COLD.

SECURING AIRPLANE

1. Brakes -- **HOLD.**
2. Electrical Equipment -- **OFF except Flashing Beacon and Navigation Lights at night.**
3. Avionics Master Switch -- **OFF.**
4. Mixture -- **IDLE CUTOFF** (pulled full out).
5. Ignition Switch -- **OFF. Place keys on glare shield.**
6. Master Switch -- **OFF.**
7. Electrical Switches -- **ALL OFF.**
8. Flight Plan -- **CLOSE.**
9. Control Lock -- **INSTALL.**

PARK AIRPLANE

1. Wings and Tail -- **TIE DOWN.**
2. Main Gear -- **CHOCK.**
3. Control Lock -- **Verify INSTALLED.**
4. Pitot Tube Cover, Nose Plugs, and Sun Screen -- **INSTALL.**
5. Hobbs, Tach, Fuel, and Oil -- **RECORD**
6. Cabin -- **CLEAN.**
7. Flight Plan -- **Verify CLOSED.**
8. Doors -- **LOCK.**

EMERGENCY PROCEDURES

TABLE OF CONTENTS

	page
Introduction	E-ii
Airspeeds for emergency Operations	E-ii
OPERATIONAL CHECKLISTS	
Engine Failures	E-1
Engine Failure During Takeoff Roll	E-1
Engine Failure Immediately After Takeoff	E-1
Engine Failure During Flight (<i>Restart Procedures</i>)	E-1
Forced Landings	E-2
Emergency Landing Without Engine Power	E-2
Precautionary Landing With Engine Power	E-2
Ditching	E-3
Fires	E-3
During Start On Ground	E-3
Engine Fire In-Flight	E-4
Electrical Fire In-Flight	E-4
Cabin Fire	E-4
Wing Fire	E-5
Icing	E-5
Inadvertent Icing Encounter	E-5
<i>Landing With a Flat Tire</i>	E-6
Landing With a Flat Main Tire	E-6
Landing With a Flat Nose Tire	E-6
Electrical Power Supply System Malfunctions	E-6
Ammeter Shows Excessive Rate of Charge (Full Scale Deflection)	E-6
Low Voltage Light Illuminates During Flight (Ammeter Shows Discharge)	E-7

INTRODUCTION

Cessna 152 Information Manual Section 3 provides checklist and amplified procedures for coping with emergencies that may occur. Emergencies caused by airplane or engine malfunctions are extremely rare if proper preflight inspections and maintenance are practiced. Enroute weather emergencies can be minimized or eliminated by careful flight planning and good judgment when unexpected weather is encountered. However, should an emergency arise, the basic guidelines described *below* should be considered and applied as necessary to correct the problem. Emergency procedures associated with ELT and other optional systems can be found in *Cessna 152 Information Manual* Section 9.

AIRSPEDS FOR EMERGENCY OPERATION

Engine Failure After Takeoff	60 KIAS
Maneuvering Speed:	
1670 Lbs	104 KIAS
1500 Lbs	98 KIAS
1350 Lbs	93 KIAS
Maximum Glide	60 KIAS
Precautionary Landing With Engine Power	55 KIAS
Landing Without Engine Power:	
Wing Flaps Up	65 KIAS
Wing Flaps Down	60 KIAS

OPERATIONAL CHECKLISTS

ENGINE FAILURES

ENGINE FAILURE DURING TAKEOFF RUN

1. Throttle -- IDLE.
2. Brakes-- APPLY.
3. Wing Flaps -- RETRACT.
4. Mixture -- IDLE CUT OFF.
5. Ignition Switch -- OFF.
6. Master Switch -- OFF.

ENGINE FAILURE IMMEDIATELY AFTER TAKEOFF

1. Airspeed -- 60 KIAS.
3. Mixture -- IDLE CUT OFF.
4. Fuel Shutoff Valve -- OFF
5. Ignition Switch -- OFF.
6. Wing Flaps -- AS REQUIRED.
7. Master Switch -- OFF.

ENGINE FAILURE DURING FLIGHT

(Restart Procedures)

1. Airspeed -- 60 KIAS
2. Carburetor Heat -- ON.
3. Primer -- IN and LOCKED.
4. Fuel Shutoff Valve -- ON.
5. Mixture -- RICH.
6. Ignition Switch -- BOTH (or START if propeller is stopped).

NOTE

If the propeller is windmilling, the engine should restart automatically within a few seconds. If the propeller has stopped (possible at low speeds), turn the ignition switch to START, advance the throttle slowly from idle and lean the mixture from full rich as required for smooth operation.

FORCED LANDINGS

EMERGENCY LANDING WITHOUT ENGINE POWER

1. Seats, Seat Belts, Shoulder Harnesses -- SECURE.
2. Airspeed -- 65 KIAS (flaps UP).
60 KIAS (flaps DOWN).
3. Mixture -- IDLE CUT OFF.
4. Fuel Shutoff Valve -- OFF.
5. Ignition Switch -- OFF.
6. Wing Flaps -- AS REQUIRED (30° recommended).
7. Master Switch -- OFF (*when landing is assured*).

NOTE

With the master switch off, wing flaps cannot be extended or retracted.

8. Doors -- UNLATCH PRIOR TO TOUCHDOWN.
9. Touchdown -- SLIGHTLY TAIL LOW.
10. Brakes -- APPLY HEAVILY.

PRECAUTIONARY LANDING WITH ENGINE POWER

1. Seats, Seat Belts, Shoulder Harnesses -- SECURE.
2. Airspeed -- 60 KIAS.
3. Wing Flaps -- 20°.
4. Selected Field -- FLY OVER, noting terrain and obstructions, then retract flaps upon reaching a safe altitude and airspeed.
5. Electrical Switches -- OFF.
6. Avionics Master Switch -- OFF.
7. Wing Flaps -- 30° (on final approach).
8. Airspeed -- 55 KIAS.
9. Master Switch -- OFF.

NOTE

With the master switch off, wing flaps cannot be extended or retracted.

10. Doors -- UNLATCH PRIOR TO TOUCHDOWN.
11. Touchdown -- SLIGHTLY TAIL LOW.
12. Ignition Switch -- OFF.
13. Brakes -- APPLY HEAVILY.

DITCHING

1. Radio -- TRANSMIT MAYDAY on 121.5 MHz, giving location and intentions *and SQUAWK 7700*.
2. Heavy Objects (in baggage area) -- SECURE OR JETTISON.
3. *Seats, Seat Belts, Shoulder Harnesses* -- SECURE.
4. Approach -- High Winds, Heavy Seas -- INTO THE WIND.
Light Winds, Heavy Swells -- PARALLEL TO SWELLS.
5. Wing Flaps -- 30°.
6. Power -- ESTABLISH 300 FT/MIN DESCENT AT 55 KIAS.
7. Cabin Doors -- UNLATCH.
8. Touchdown -- LEVEL ATTITUDE AT 300 FT/MIN DESCENT.
9. Face -- CUSHION at touchdown with folded coat.
10. Airplane -- EVACUATE through cabin doors. If necessary, open window and flood cabin to equalize pressure so doors can be opened.
11. Life Vests and Raft -- INFLATE *WHEN CLEAR OF AIRPLANE*.
The aircraft cannot be depended on for flotation for more than a few minutes.

FIRES**DURING START ON GROUND**

1. Cranking – CONTINUE, to get a start which would suck the flames and accumulated fuel through the carburetor and into the engine.

If engine starts:

2. Power -- 1700 RPM for a few minutes.
3. Engine -- SHUTDOWN and inspect for damage.

If engine fails to start:

4. Cranking – CONTINUE in an effort to obtain a start.
5. Fire Extinguisher -- OBTAIN (have ground attendants obtain if not installed).
6. Engine -- SECURE.
 - a. Master Switch -- OFF.
 - b. Ignition Switch -- OFF.
 - c. Fuel Shutoff Valve -- OFF.
7. Fire -- EXTINGUISH using fire extinguisher, wool blanket, or dirt.
8. Fire Damage -- INSPECT, repair damage or replace damaged components or wiring before conducting another flight.

ENGINE FIRE IN FLIGHT

1. Mixture -- IDLE CUT OFF.
2. Fuel Shutoff Valve -- OFF.
3. Master Switch -- OFF.
4. Cabin Heat and Air -- OFF (except overhead vents).
5. Airspeed -- 85 KIAS (If fire is not extinguished, increase glide speed to find an airspeed - *within airspeed limitations* - which will provide an incombustible mixture).
6. Forced Landing -- EXECUTE (as described in Emergency Landing Without Engine Power).

ELECTRICAL FIRE IN FLIGHT

1. Master Switch -- OFF.
2. All Other Switches (except ignition switch) -- OFF.
3. Vents/Cabin Air/Heat -- CLOSED.
4. Fire Extinguisher—ACTIVATE (if available).

WARNING

After discharging an extinguisher within a closed cabin *and ascertaining that fire has been extinguished*, ventilate the cabin.

If fire appears out and electrical power is necessary for continuance of flight *to nearest suitable airport or landing area*:

6. Master Switch -- ON.
7. Circuit Breakers -- CHECK for faulty circuit, do not reset.
8. Avionics Master Switch – ON *if essential for continuation of flight*.
9. *Essential* Radio/Electrical Switches -- ON one at a time, with delay after each until short circuit is localized.
10. Vents/Cabin Air/Heat -- OPEN when it is ascertained that fire is completely extinguished.

CABIN FIRE

1. Master Switch -- OFF.
2. Vents/Cabin Air/Heat -- CLOSED (to avoid drafts).
3. Fire Extinguisher—ACTIVATE (if available).

WARNING

After discharging an extinguisher within a closed cabin *and ascertaining that fire has been extinguished*, ventilate the cabin.

4. Vents/Cabin Air/Heat -- OPEN when it is ascertained that fire is completely extinguished.
5. Land the airplane as soon as possible to inspect for damage.

WING FIRE

1. Landing/Taxi Light Switches – OFF (aircraft with lights in wing).
2. Navigation Light Switch -- OFF.
3. Pitot Heat Switch -- OFF.

NOTE

Perform a sideslip to keep the flames away from the fuel tank and cabin and land as soon as possible with flaps retracted.

ICING**INADVERTENT ICING ENCOUNTER**

1. Turn pitot heat switch ON.
2. Turn back or change altitude to obtain an outside air temperature that is less conducive to icing.
3. Pull cabin heat control full out to obtain maximum defroster air temperature. For greater airflow at reduced temperatures, adjust the cabin air control as required.
4. Open the throttle to increase engine speed and minimize ice build- up on propeller blades.
5. Watch for signs of carburetor air filter ice and apply carburetor heat as required. An unexplained loss in engine speed could be caused by carburetor ice or air intake filter ice. Lean the mixture for maximum RPM, if carburetor heat is used continuously.
6. Plan a landing at the nearest airport. With an extremely rapid ice buildup, select a suitable "off airport" landing site.
7. With an ice accumulation of ¼ inch or more on the wing leading edges, be prepared for significantly higher stall speed *and a longer landing roll*.
8. Leave wing flaps retracted. With a severe ice buildup on the horizontal tail, the change in wing wake airflow direction caused by wing flap extension could result in a loss of elevator effectiveness.
9. Open left window and, if practical, scrape ice from a portion of the windshield for visibility in the landing approach.
10. Perform a landing approach using a forward slip, if necessary, for improved visibility.
11. Approach at 65 to 75 KIAS depending upon the amount of the accumulation.
12. Perform a landing in level attitude.

LANDING WITH A FLAT TIRE**LANDING WITH A FLAT MAIN TIRE**

1. Wing Flaps – AS DESIRED.
2. Approach -- NORMAL.
3. Touchdown -- GOOD MAIN TIRE FIRST, hold airplane off flat tire as long as possible *with aileron control*.
4. *Directional Control -- MAINTAIN using brake on good wheel as required.*

LANDING WITH A FLAT NOSE TIRE

1. Approach -- NORMAL.
2. Flaps -- AS REQUIRED.
3. Touchdown -- ON MAINS, hold nose wheel off the ground as long as possible.
4. When nose wheel touches down, maintain full up elevator as airplane slows to stop.

ELECTRICAL POWER SUPPLY SYSTEM MALFUNCTIONS**AMMETER SHOWS EXCESSIVE RATE OF CHARGE (Full Scale Deflection)**

1. Alternator -- OFF.
2. Alternator Circuit Braker – PULL.
3. Nonessential Electrical Equipment -- OFF.
4. Flight -- TERMINATE as soon as practical.

LOW-VOLTAGE LIGHT ILLUMINATES DURING FLIGHT (Ammeter Shows Discharge)

NOTE

Illumination of the low-voltage light may occur during low RPM conditions with an electrical load on the system such as during low RPM taxi. Under these conditions, the light will go out at higher RPM. The master switch need not be recycled since an over-voltage condition has not occurred to de-activate the alternator system.

1. *Ammeter -- SHOWS DISCHARGE.*
2. *Avionics Master Switch -- OFF.*
3. *Alternator Circuit Breaker -- CHECK IN.*
4. *Master Switch -- OFF (both sides) for a few seconds.*
5. *Master Switch -- ON.*
6. *Low-Voltage Light -- CHECK OFF.*
7. *Avionics Master Switch -- ON.*

If Ammeter still shows discharge:

8. *Alternator -- OFF.*
9. *Nonessential Radio and Electrical Equipment -- OFF.*
10. *Flight -- TERMINATE as soon as practical.*